

- characteristics, 899
- DBR, 882
- DFB, 887
- distributed Bragg reflector, 882
- distributed feedback, 887
- edge-emitting, 881
- efficiency, 905
- Fabry–Perot, 881
- folded-cavity surface-emitting, 893
- grating-coupled surface-emitting, 893
- modulation characteristics, 908
- power, 902
- spectrum, 907
- surface-emitting, 892
- vertical-cavity surface-emitting, 894
- semiconductor laser amplifier, 875
- semiconductor optical amplifier, 875
- sensor
 - current, 319
 - magnetic field, 319
 - magneto-optic, 317
- separate absorption and multiplication, 994
- SFG, 460
- SH, 838
- Schawlow–Townes limit, 708
- Schawlow–Townes relation, 708
- shear strain, 359
- SHG, 460
- Shockley–Read recombination, 778
- shot noise, 927, 929
 - excess, 931
- shot-noise limited, 933
- Shubnikov’s groups, 293
- Si, 761
- SI base units, 1027
- SiC, 761
- SI derived units, 1027
- SiGe, 761
- signal-to-noise current ratio, 928
- signal-to-noise ratio, 662, 928, 933
 - power, 928
- signal wave, 506, 508
- silica fiber, 119
- single heterostructure, 838, 841
- single-mode fiber, 120, 128
- single-mode waveguide, 92
- slab waveguide, 84
- slope efficiency, 659, 716
- slow axis, 32
- slowly varying amplitude approximation, 166
- small-area surface-emitting device, 853
- small-signal gain coefficient, 645
- small-signal power gain, 653
- Snell’s law, 45
- SNR, 662, 928
- soliton, 119, 154, 441, 468
- space-charge region, 799
- spatial beam walk-off, 37
- spatial inversion, 5, 240, 292
- spatial-inversion symmetry, 292
- spatial light filter, 522
- spatial light modulator, 322
 - binary phase-only mode, 325
 - reflection-mode, 325
 - transmission-mode, 323
 - ternary phase-only mode, 325
- spatial nonlocality, 7
- spatial symmetry, 451
- specific detectivity, 940
- specific Faraday rotation, 300
- spectral envelope, 732
- spectral hole burning, 707
- spectral lineshape, 614
- spectral response, 935
- spectral width, pulse, 732
- speed of light, 12
- SPM, 464
- spontaneous Brillouin scattering, 536
- spontaneous carrier recombination, 784
- spontaneous carrier recombination rate, 818
- spontaneous carrier relaxation rate, 909
- spontaneous emission, 614, 649, 835
 - amplified, 661
- spontaneous emission factor, 661
- spontaneous emission noise, 661
- spontaneous emission power, 648
- spontaneous magnetization, 290
- spontaneous radiative lifetime, 616, 625
- spontaneous Raman scattering, 532
- spontaneous Stokes emission, 541
- spot size, 40
- SQW, 839
- SRS, 464
- stability for Fabry–Perot cavity, 695
- staircase APD, 997
- standing wave, 358
- standing-wave modulator, acousto-optic, 398
- static magnetic field, 291
- static magnetization, 292
- step-index fibers, 120
- step-index waveguide, 74, 84
- stimulated Brillouin scattering, 464, 531, 536
- stimulated emission, 614
- stimulated Raman scattering, 464, 465, 531
- Stokes–anti-Stokes coupling, 542, 579
- Stokes frequency, 465
- Stokes process, 477
- Stokes transition, 465
- stop band of DFB laser, 889
- strain, 244
 - shear, 359
 - tensile, 359
- strain-optic coefficient, 360
- strain tensor, 359