

WS 1.3 Linearity and intermodulation distortion

© 2017 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

Section 1.6.4 Single carrier transfer characteristics

Simple functions which can be made a good fit to experimental data for TWTs are given in:

A. A. M. Saleh, "Frequency-Independent and Frequency-Dependent Nonlinear Models of TWT Amplifiers," *IEEE Transactions on Communications*, vol. 29, pp. 1715-1720, (1981).

Input power in dB normalised to saturation at $r = 1$ $D1(r) := 20 \cdot \log(r)$

Empirical constants defining the AM/AM and AM/PM transfer curves are adjusted to fit simulated or experimental data

$$\alpha_a := 2$$

$$\beta_a := 1$$

$$\alpha_\phi := -2.53$$

$$\beta_\phi := 2.8$$

AM/AM curve $Am(r) := \frac{\alpha_a \cdot r}{1 + \beta_a \cdot r^2}$ Equation 1.56

AM/PM curve $\Phi_m(r) := \frac{\alpha_\phi \cdot r^2}{1 + \beta_\phi \cdot r^2}$ Equation 1.57

AM/AM conversion at the second harmonic might be modelled by a similar function with constants

$$\alpha_h := 3$$

$$\beta_h := 1.5$$

$$Bm(r) := \frac{\alpha_h \cdot r^2}{(1 + \beta_h \cdot r^2)^2}$$
 Equation 1.58

Output power in dB normalised to saturation

$$D2(r) := 20 \cdot \log(Am(r))$$

Output power in dB at the second harmonic normalised to saturation


$$Dh(r) := 20 \cdot \log(Bm(r))$$

Linear extrapolations of the small-signal curves

$$Dhh(r) := 2 \cdot D1(r) + 20 \cdot \log(\alpha_h)$$

$$D22(r) := D1(r) + 20 \cdot \log(\alpha_a)$$

Plot the characteristics on linear scales



Plotting range for r $r := 0.01, 0.04 \dots 4$




Figure 1.4

Compare Figure 14.23(a)




Figure 1.5

Compare Figure 14.24

Two-tone intermodulation products


Define the input signal in the time domain with two equal carriers with amplitude $\frac{V_1}{\sqrt{2}}$ at frequencies $(n+1)$ and $(n-1)$ so that the total carrier power is equal to that of a single carrier with amplitude V_1

 $n := 10$

Envelope $r(V_1, \phi) := \sqrt{2} \cdot V_1 \cdot \sin(\phi)$ Note $\phi = \Delta\omega \cdot t$

Input waveform $V_{in}(V_1, \phi) := r(V_1, \phi) \cdot \cos(n \cdot \phi)$ Equation 1.50

Plot the input waveform with $V_1 := \sqrt{2}$

Figure 1.16(a)

The output voltage in the time domain is found using the AM/AM and AM/PM curves defined above.

$$V_2(V_1, \phi, \phi_s) := \text{Am}(r(V_1, \phi)) \cdot \cos(n \cdot \phi + \phi_s \cdot \Phi_m(r(V_1, \phi))) \quad \text{Equation 1.51}$$

The parameter ϕ_s is zero if the AM/PM characteristics are ignored and 1 if they are included

Plot the output voltage waveform




Figure 1.16(b)

The amplitudes of the harmonics of the output waveform are found by Fourier analysis

$$V_{10}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n+1) \cdot \phi] d\phi \quad V_{10}(1, 1) = 0.461$$

$$V_{01}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n-1) \cdot \phi] d\phi \quad V_{01}(1, 1) = -0.461$$

$$V_{21}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n+3) \cdot \phi] d\phi \quad V_{21}(1, 1) = 0.164$$

$$V_{12}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n-3) \cdot \phi] d\phi \quad V_{12}(1, 1) = -0.164$$


$$V_{32}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n+5) \cdot \phi] d\phi \quad V_{32}(1, 1) = 0.057$$

$$V_{23}(V_1, \phi_s) := \frac{1}{\pi} \cdot \int_{-\pi}^{\pi} V_2(V_1, \phi, \phi_s) \cdot \sin[(n-5) \cdot \phi] d\phi \quad V_{23}(1, 1) = -0.057$$

Total carrier, third order and fifth order intermodulation powers in dB

$$D_{10}(V_1, \phi_s) := 10 \cdot \log\left(2 V_{10}(V_1, \phi_s)^2\right) \quad D_{21}(V_1, \phi_s) := 10 \cdot \log\left(2 V_{21}(V_1, \phi_s)^2\right) \quad D_{32}(V_1, \phi_s) := 10 \cdot \log\left(2 V_{32}(V_1, \phi_s)^2\right)$$

Plotting range for the input voltage $V_1 := 0, 0.01 \dots 10.0$



- +++ Single carrier
- ▣▣▣ Carriers (AM/AM only)
- ◇◇◇ IM3 (AM/AM only)
- ⊖⊖⊖ IM5 (AM/AM only)
- ■ ■ Carriers (with AM/PM)
- ◆ ◆ ◆ IM3 (with AM/PM)
- ● ● IM5 (with AM/PM)

Figure 1.15 (corrected)

Compare Figure 2 in: Stette, G. R.
 "Calculation of Intermodulation from a Single Carrier Amplitude
 Characteristic."
 IEEE Transactions on Communications **22**(3): 319-323.(1974).