

Worksheet 7.5 Periodic Electrostatic Focusing

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

This worksheet calculates the beam edge profile for a beam with periodic electrostatic focusing. See section 7.6.3

The parameters β , U_1 are set and the differential equations governing the beam edge are solved given the initial normalised radius (R) and slope ($dR/d\theta$) of the beam edge. The axial variation of the electric field is as $\cos Z$.

The maximum value of the normalised time θ and the number of integrations steps are set.

$$\beta := 0.01$$

$$U_1 := 0.351$$

$$R_0 := 1$$

$$R1_0 := 0$$

$$\theta_{\max} := 12 \cdot \pi$$

$$nsteps := 1000$$

The section below can be collapsed to allow the input parameters and the results to be displayed on the same screen.



$$\theta = \beta_0 \cdot u_0 \cdot t$$

$$R = \frac{r}{r_0}$$

$$Z = \beta_0 \cdot z$$

$$\beta = \frac{1}{2} \cdot \frac{\beta_p^2}{\beta_0^2}$$

$$U_1 = \frac{V_1}{V_0}$$

$$\frac{d^2 R}{d\theta^2} = \beta \frac{1}{R} + \frac{1}{4} U_1 R \cos(Z) \quad \text{Equation 7.111}$$

$$\frac{d^2 Z}{d\theta^2} = -\frac{1}{2} U_1 \sin(Z) \quad \text{Equation 7.112}$$

The differential equation is solved for the initial conditions $R = R_0$ and $dR/d\theta = R1_0$

$$D(\theta, R1) := \begin{pmatrix} R1_1 \\ \frac{\beta}{R1_0} - \frac{U_1}{4} \cdot R1_0 \cdot \cos(R1_2) \\ R1_3 \\ \frac{1}{2} \cdot U_1 \cdot \sin(R1_2) \end{pmatrix}$$

$$\begin{pmatrix} R1_0 \\ R1_1 \\ R1_2 \\ R1_3 \end{pmatrix} = \begin{pmatrix} R \\ \frac{dR}{d\theta} \\ Z \\ \frac{dZ}{d\theta} \end{pmatrix}$$

The paraxial ray equations referred to the injection radius are expressed as simultaneous first order equations

$$R1 := \begin{pmatrix} R_0 \\ R1_0 \\ 0 \\ \sqrt{1 - U_1} \end{pmatrix}$$

$$\Theta := \text{AdamsBDF}(R1, 0, \theta_{\max}, \text{nsteps}, D)$$

The solution to the differential equations is contained in the matrix Θ . The first column contains the normalised time θ , and the remaining columns contain R , $dr/d\theta$, Z and $dZ/d\theta$.

$$R_{\min} := \min(\Theta^{\langle 1 \rangle}) \quad R_{\max} := \max(\Theta^{\langle 1 \rangle}) \quad \text{ripple} := \frac{\max(\Theta^{\langle 1 \rangle}) - \min(\Theta^{\langle 1 \rangle})}{\max(\Theta^{\langle 1 \rangle}) + \min(\Theta^{\langle 1 \rangle})} \quad R_{\text{mean}} := 0.5 \cdot (\max(\Theta^{\langle 1 \rangle}) + \min(\Theta^{\langle 1 \rangle}))$$

Find the ripple as a function of β and U_1 and, hence find the value of U_1 that minimises the ripple.

$$\begin{aligned} \text{Ripple}(\beta, U_1) := & \left| \begin{array}{l} R1 \leftarrow \begin{pmatrix} R_0 \\ R1_0 \\ 0 \\ \sqrt{1 - U_1} \end{pmatrix} \\ D(\theta, R1) \leftarrow \begin{pmatrix} R1_1 \\ \frac{\beta}{R1_0} - \frac{U_1}{4} \cdot R1_0 \cdot \cos(R1_2) \\ R1_3 \\ \frac{1}{2} \cdot U_1 \cdot \sin(R1_2) \end{pmatrix} \\ \Theta \leftarrow \text{AdamsBDF}(R1, 0, \theta_{\max}, \text{nsteps}, D) \\ \text{Ripple} \leftarrow \frac{\max(\Theta^{\langle 1 \rangle}) - \min(\Theta^{\langle 1 \rangle})}{\max(\Theta^{\langle 1 \rangle}) + \min(\Theta^{\langle 1 \rangle})} \\ \text{return Ripple} \end{array} \right| \\ \text{Rip}(U_1) := & |\text{Ripple}(\beta, U_1)| \\ U_{1\min} := & \text{Minimize}(\text{Rip}, U_1) \end{aligned}$$






Figure 7.15

$$\beta = 0.01$$

$$U_1 = 0.351$$

$$R_{\min} = 0.825$$

$$R_{\max} = 1$$

$$R_{\text{mean}} = 0.912$$

$$\text{ripple} = 9.6\%$$

Minimum ripple solutions

The minimum ripple solution is obtained by finding the minimum value of U_1 for which $R_{\max} = 1$.

Copy the results into the data table. The first column is β , the second is the value of U_1 for minimum ripple and the third is the ripple.

$$U_{1\min} = 0.350$$

$$\text{Ripple}(\beta, U_{1\min}) = \blacksquare$$

X0 :=

	0	1	2
0	0	0	0
1	$1 \cdot 10^{-3}$	0.106	0.027
2	$2.5 \cdot 10^{-3}$	0.17	0.043
3	$5 \cdot 10^{-3}$	0.243	0.062
4	0.01	0.35	0.093
5	0.015	0.434	0.119
6	0.02	0.506	0.145
7	0.025	0.57	0.171
8	0.03	0.63	0.199
9	0.035	0.686	0.231
10	0.04	0.731	0.269




Figure 7.16




Figure 7.17