

## WS 3.6 Iris-coupled cavity

© 2017 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

### Section 3.6.2 Iris coupling

This sheet illustrates the properties of a rectangular cavity coupled to a rectangular waveguide having the same width and height by an inductive iris of width  $w$  in a thin wall.

Set the waveguide and cavity dimensions (WG10)


$$a := 72\text{-mm}$$

$$b := 34\text{-mm}$$

$$d := 1.0a$$

$$w := 0.15 \cdot a$$

The region below can be collapsed to allow the results to appear on the same screen as the data.





### Calculate the surface resistance

Conductivity of copper

$$\sigma := 5.959 \cdot 10^7 \cdot \text{S} \cdot \text{m}^{-1}$$

r.m.s. surface roughness

$$\Delta := 0.1 \cdot \mu\text{m}$$

$$\delta s(\omega) := \sqrt{\frac{2}{\omega \cdot \sigma \cdot \mu_0}}$$

$$R_s(\omega) := \frac{1}{\sigma \cdot \delta s(\omega)}$$

Equation 3.50

Effect of r.m.s. surface roughness  $\Delta$

$$R_{rs}(x) := 1 + \frac{2}{\pi} \cdot \text{atan}(1.4 \cdot x^2)$$

Equation 3.56

Surface resistance

$$R_r(\omega) := R_s(\omega) \cdot R_{rs}\left(\frac{\Delta}{\delta s(\omega)}\right)$$

### Calculate cavity parameters

Resonant frequency

$$\omega_0 := c \cdot \sqrt{\left(\frac{\pi}{a}\right)^2 + \left(\frac{\pi}{d}\right)^2}$$

$$f_0 := \frac{\omega_0}{2 \cdot \pi}$$

Skin depth

$$\delta s(\omega_0) = 1.202 \cdot \mu\text{m}$$

$$f_0 = 2.944 \cdot \text{GHz}$$

R/Q

$$R_Q := \frac{4}{\pi} \cdot \frac{b}{\sqrt{a^2 + d^2}} \cdot \sqrt{\frac{\mu_0}{\epsilon_0}}$$

$$R_Q = 160.2 \cdot \Omega$$

Unloaded Q

$$Q := \frac{\pi}{4 \cdot R_r(\omega_0)} \cdot \sqrt{\frac{\mu_0}{\epsilon_0}} \cdot \left[ \frac{2 \cdot b \cdot (a^2 + d^2)^{1.5}}{a \cdot d \cdot (a^2 + d^2) + 2 \cdot b \cdot (a^3 + d^3)} \right]$$

Equation 3.64

$$Q = 14463$$

Shunt resistance

$$R_C := R_Q \cdot Q$$

$$R_C = 2.317 \cdot \text{M}\Omega$$

**Calculate waveguide parameters**

Cut-off frequency  $\beta_c := \frac{\pi}{a}$   $\omega_c := c \cdot \beta_c$   $f_c := \frac{\omega_c}{2 \cdot \pi}$   $f_c = 2.082 \cdot \text{GHz}$

Guide wavelength  $\beta_g(\omega) := \sqrt{\frac{\omega^2}{c^2} - \beta_c^2}$


Characteristic impedance  $Z_{PV}(\omega) := 2 \cdot \frac{b}{a} \cdot \left( \frac{\omega}{c \cdot \beta_g(\omega)} \cdot \sqrt{\frac{\mu_0}{\epsilon_0}} \right)$   $Z_{PV}(\omega_0) = 503.2 \Omega$

**Calculate normalised iris susceptance**

$$bi(\omega, w) := -\frac{2 \cdot \pi}{\beta_g(\omega) \cdot a} \cdot \cot\left(\frac{\pi \cdot w}{2 \cdot a}\right)^2$$

**1. Distributed element equivalent circuit model**

The cavity loss is represented by a shunt resistor  $R_c$  at the centre of the cavity. The normalised input admittance is calculated using transmission line analysis.



Normalised cavity conductance

$$g_C(\omega) := \frac{Z_{PV}(\omega)}{R_C}$$

Admittance at 1

$$y_{11}(\omega) := \frac{1}{j \cdot \tan\left(\beta_g(\omega) \cdot \frac{d}{2}\right)}$$

Admittance at 2

$$y_{12}(\omega) := y_{11}(\omega) + g_C(\omega)$$

Admittance at 3

$$y_{13}(\omega) := \frac{y_{12}(\omega) + j \cdot \tan\left(\beta_g(\omega) \cdot \frac{d}{2}\right)}{1 + j \cdot y_{12}(\omega) \cdot \tan\left(\beta_g(\omega) \cdot \frac{d}{2}\right)}$$

### Input admittance and reflection coefficient

$$y_{in}(\omega, w) := y_{13}(\omega) + j \cdot b_i(\omega, w) \quad z_{in}(\omega, w) := \frac{1}{y_{in}(\omega, w)}$$

$$\rho(\omega, w) := \frac{z_{in}(\omega, w) - 1}{z_{in}(\omega, w) + 1}$$

$$S_{11}(\omega, w) := 20 \cdot \log(|\rho(\omega, w)|)$$

$$\phi_1(\omega, w) := \text{atan2}(\text{Re}(\rho(\omega, w)), \text{Im}(\rho(\omega, w)))$$

### Find the detuned resonant frequency where the input admittance is real

$$\omega_1(w) := \text{root}(\text{Im}(y_{in}(\omega_0, w)), \omega_0)$$

$$\frac{\omega_1(w)}{\omega_0} = 0.99547$$

Shift the phase so that the diameter of the resonant circle lies on the real axis of the Smith chart

$$\phi(\omega, w) := \begin{cases} \left( \phi_1(\omega, w) - \phi_1(\omega_1(w), w) \right) & \text{if } \left| \phi_1(\omega_1(w), w) \right| \leq \frac{\pi}{2} \\ \phi_1(\omega, w) - \phi_1(\omega_1(w), w) - \pi & \text{otherwise} \end{cases}$$

Find the diameter of the resonant circle and the coupling coefficient from (24) in Kajfez, D. (1984). "Q-factor measurement with network analyser." IEEE Transactions on Microwave Theory and Techniques **MTT-32**(7): 666-670.

$$\text{dia}(w) := \begin{cases} \left( 1 + \left| \rho(\omega_1(w), w) \right| \right) & \text{if } \left| \phi_1(\omega_1(w), w) \right| \leq \frac{\pi}{2} \\ \left( 1 - \left| \rho(\omega_1(w), w) \right| \right) & \text{otherwise} \end{cases}$$

$$\kappa(w) := \frac{\text{dia}(w)}{2 - \text{dia}(w)}$$

$$\kappa(w) = 3.735$$

Find the co-ordinates of the points which are at angles +/-  $\alpha$

$$\alpha := 45 \cdot \text{deg}$$

$$\Gamma_1(w) := \sqrt{1 + \text{dia}(w)^2 \cos(\alpha)^2 - 2 \cdot \text{dia}(w) \cdot \cos(\alpha)^2}$$

$$\Gamma_1(w) = 0.817$$

$$\theta_1(w) := \pi - \text{asin}\left(\frac{\text{dia}(w)}{\Gamma_1(w)} \cdot \sin(\alpha) \cdot \cos(\alpha)\right)$$

$$\pi - \theta_1(w) = 1.309$$

$$\theta_2(w) := \pi - \text{asin}\left(\frac{\text{dia}(w)}{\Gamma_1(w)} \cdot \sin(-\alpha) \cdot \cos(\alpha)\right)$$

$$\pi - \theta_2(w) = -1.309$$

Find the loaded Q from the frequencies at these two points

```

 $Q_L(w) := \left| \begin{array}{l} \omega_{1U} \leftarrow 1.1 \cdot \omega_1(w) \\ \omega_{1L} \leftarrow 0.9 \cdot \omega_1(w) \\ \omega_{2U} \leftarrow 1.1 \cdot \omega_1(w) \\ \omega_{2L} \leftarrow 0.9 \cdot \omega_1(w) \\ \Gamma_1 \leftarrow \Gamma_1(w) \\ f(\omega) \leftarrow (|\rho(\omega, w)| - \Gamma_1) \\ \text{for } n \in 1..1000 \\ \quad \left| \begin{array}{l} \omega_n^1 \leftarrow 0.5 \cdot (\omega_{1U} + \omega_{1L}) \\ \omega_{1U} \leftarrow \omega_n^1 \text{ if } f(\omega_n^1) > 0 \\ \omega_{1L} \leftarrow \omega_n^1 \text{ if } f(\omega_n^1) < 0 \\ \omega_n^2 \leftarrow 0.5 \cdot (\omega_{2U} + \omega_{2L}) \\ \omega_{2U} \leftarrow \omega_n^2 \text{ if } f(\omega_n^2) < 0 \\ \omega_{2L} \leftarrow \omega_n^2 \text{ if } f(\omega_n^2) > 0 \\ Q_n \leftarrow \begin{cases} \frac{\omega_0 \cdot \tan(\alpha)}{\omega_n^1 - \omega_n^2} & \text{if } \omega_n^1 - \omega_n^2 \neq 0 \\ 0 & \text{otherwise} \end{cases} \\ (\text{break}) \text{ if } Q_n \neq 0 \wedge |Q_n - Q_{n-1}| < 0.0001 \end{array} \right. \\ \text{return } Q_n \end{array} \right.$ 

```

$$Q_L(w) = 3048$$

Calculate the unloaded Q and compare it with the value calculated above

$$Q_0(w) := Q_L(w) \cdot (1 + \kappa(w))$$

$$Q = 14463$$

$$Q_0(w) = 14431$$

Plot the results

$$\omega_{\text{start}} := \left(1 - \frac{5}{Q_L(w)}\right) \cdot \omega_1(w) = 1.839 \times 10^{10} \frac{1}{s}$$

$$\omega_{\text{stop}} := \left(1 + \frac{5}{Q_L(w)}\right) \cdot \omega_1(w) = 1.845 \times 10^{10} \frac{1}{s}$$

$$\omega_{\text{step}} := \frac{\omega_{\text{stop}} - \omega_{\text{start}}}{200}$$

Marker co-ordinates

$$\Gamma_m(w) := \begin{pmatrix} 1 \\ \Gamma_1(w) \\ 1 \\ \Gamma_1(w) \\ 1 \end{pmatrix} \quad \theta_m(w) := \begin{pmatrix} 0.5 \cdot \pi \\ \theta_1(w) \\ \pi \\ \theta_2(w) \\ 1.5 \cdot \pi \end{pmatrix}$$

$$\omega_p := \omega_{\text{start}}, (\omega_{\text{start}} + \omega_{\text{step}}) \dots \omega_{\text{stop}}$$

$$\text{dB} := 1$$



**Results: Coupling factor, Unloaded and loaded Q, resonant frequency, and S11 at resonance**

$$\kappa(\omega) = 3.735$$

$$Q_0(\omega) = 14431$$


$$Q_L(\omega) = 3048$$

$$\frac{\omega_1(\omega)}{2 \cdot \pi} = 2.931 \cdot \text{GHz}$$

$$\frac{\omega_1(\omega)}{\omega_0} = 0.995$$

$$S_{11}(\omega_1(\omega), \omega) = -4.8 \text{ dB}$$

Note: this calculation only converges reliably for a limited range of input parameters



Normalised frequency





Figure 3.24

Markers show the loaded resonant frequency and 3dB points



## 2. Lumped element equivalent circuit model

The cavity inductance is divided into two parts determined by the parameter  $k$  since only part of the current circulating in the cavity is intercepted by the iris.



Lumped element parameters

$$C_C := \frac{1}{\omega_0 \cdot R_Q}$$

$$L_C := \frac{R_Q}{\omega_0}$$

$$C_C = 0.338 \cdot \text{pF}$$

$$L_C = 0.0087 \cdot \mu\text{H}$$

$$R_C = 2.32 \cdot \text{M}\Omega$$

Admittance and impedance of the cavity

$$Y_{21}(k, \omega) := j \cdot \omega \cdot C_C + \frac{1}{R_C} + \frac{1-k}{j \cdot \omega \cdot L_C} \quad Z_{21}(k, \omega) := \frac{1}{Y_{21}(k, \omega)}$$

Impedance presented by the cavity at the plane of the iris

$$Z_{22}(k, \omega) := \frac{j \cdot \omega \cdot L_C}{k} + Z_{21}(k, \omega)$$

Normalised admittance at the plane of the iris

$$y_{22}(k, \omega) := \frac{Z_{PV}(\omega)}{Z_{22}(k, \omega)}$$

Resonant frequency

$$\omega_2(k, w) := \text{root}(\text{Im}(y_{22}(k, \omega_0)) + j \cdot \text{bi}(\omega_0, w)), \omega_0)$$

Current fraction to give the correct resonant frequency

$$kk := 0.3$$

$$k := \text{root}(\omega_1(w) - \omega_2(kk, w), kk)$$

$$k = 0.321$$

Check

$$\frac{\omega_2(k, w)}{\omega_1(w)} = 1$$