

WS 6.3 Electrostatic solution for a tetrode

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

Dimensions in millimetres

$$a := 1$$

$$r := 0.05$$

$$d_1 := 0.442$$

$$d_2 := 0.620$$


$$d_3 := 9.983$$

Electrode potentials

$$V_g := 20 \cdot V$$

$$V_s := 900 \cdot V$$

$$V_a := 6000 \cdot V$$



The working equations are

$$f_s(x, y) := \frac{a}{4 \cdot \pi} \cdot \ln \left[\frac{\cosh \left[\frac{2 \cdot \pi \cdot (x + d_1 + d_2)}{a} \right] - \cos \left(\frac{2 \cdot \pi \cdot y}{a} \right)}{\cosh \left[\frac{2 \cdot \pi \cdot (x - d_1 - d_2)}{a} \right] - \cos \left(\frac{2 \cdot \pi \cdot y}{a} \right)} \right] \quad \text{Equation 6.76}$$

$$D_s := -\frac{a}{2 \cdot \pi \cdot d_3} \cdot \ln \left(2 \cdot \sin \left(\frac{\pi \cdot r}{a} \right) \right) \quad \text{Equation 6.77}$$

$$D_s = 0.019$$

$$\frac{1}{D_s} = 54$$

$$f_g(x, y) := \frac{a}{4 \cdot \pi} \cdot \ln \left[\frac{\cosh \left[\frac{2 \cdot \pi \cdot (x + d_1)}{a} \right] - \cos \left(\frac{2 \cdot \pi \cdot y}{a} \right)}{\cosh \left[\frac{2 \cdot \pi \cdot (x - d_1)}{a} \right] - \cos \left(\frac{2 \cdot \pi \cdot y}{a} \right)} \right] \quad \text{Equation 6.24}$$

$$D_g := -\frac{a}{2 \cdot \pi \cdot d_2} \cdot \ln \left(2 \cdot \sin \left(\frac{\pi \cdot r}{a} \right) \right) \quad \text{Equation 6.81}$$

$$D_g = 0.298$$

$$\frac{1}{D_g} = 3.4$$

$$A1 := \begin{pmatrix} d_1 + d_2 \cdot D_g & d_1 & d_1 \\ d_1 & d_1 + d_2 + d_3 \cdot D_s & d_1 + d_2 \\ d_1 & d_1 + d_2 & d_1 + d_2 + d_3 \end{pmatrix} \quad \text{Equation 6.82}$$

$$\frac{1}{D_s \cdot D_g} = 181$$

$$V_t(x, y) := \begin{pmatrix} f_g(x, y) & f_s(x, y) & x \end{pmatrix} \cdot (A1)^{-1} \cdot \begin{pmatrix} V_g \\ V_s \\ V_a \end{pmatrix} \quad \text{Equation 6.75}$$

Generate a matrix for a potential plot

$n := 50$

```

Vt_plot :=
  for i ∈ 0..⌊(d1 + d2 + d3)/a⌋·n
    for j ∈ 0..n
      x ← i/n·a
      y ← j/n·a
      Vj,i ←
        Vg if [(x - d1)2 + y2] ≤ r2 ∨ [(x - d1)2 + (a - y)2] ≤ r2
        Vs if [(x - d1 - d2)2 + y2] ≤ r2 ∨ [(x - d1 - d2)2 + (a - y)2] ≤ r2
        Vt(x, y) otherwise
    return V

```

Calculate electron trajectories

$$E_x(x, y) := \frac{d}{dx} V_t(x, y) \cdot \frac{1}{V} \quad E_y(x, y) := \frac{d}{dy} V_t(x, y) \cdot \frac{1}{V} \quad \eta := -1.759 \cdot 10^{11}$$

Estimate the maximum flight time

$$d_{\max} := d_1 + d_2 + d_3 \quad s = \frac{1}{2} \cdot a \cdot t^2 \quad t = \sqrt{\frac{2 \cdot s}{a}} \quad t_{\max} := 1.5 \cdot \sqrt{\frac{2 \cdot d_{\max}^2 \cdot V}{|\eta| \cdot V_a}} \quad t_{\max} = 7.212 \times 10^{-7}$$

Set up the simultaneous first order differential equations for the electron motion

$$Dt(t, z) := \begin{pmatrix} \eta \cdot E_x(z_1, z_3) \\ z_0 \\ \eta \cdot E_y(z_1, z_3) \\ z_2 \end{pmatrix}$$

$$\frac{d}{dt} v_x = \eta \cdot E_x$$

$$\frac{d}{dt} x = v_x$$

$$\frac{d}{dt} v_y = \eta \cdot E_y$$

$$\frac{d}{dt} y = v_y$$

Number of time steps and number of trajectories

nsteps := 1000

ntraj := 25

```
Z := | for n ∈ 0..ntraj
      |   |
      |   |   init ← ( 0
      |   |   |   0
      |   |   |   0
      |   |   |   a·n
      |   |   |   2·ntraj
      |   |   |
      |   |   Z_n ← AdamsBDF(init, 0, t_max, nsteps, Dt)
      |   |
      |   | return Z
```

The matrix Z contains the time in the first column then, in groups of four columns v_x , x , v_y and y for each trajectory.

Unpack the solution matrix

<pre> xn := nmax ← 2·ntraj for n ∈ 0..nmax for i ∈ 0..nsteps xn_{i,n} ← $\begin{cases} \left[\left(Z_n \right)^{\langle 2 \rangle} \right]_i & \text{if } n \leq \text{ntraj} \\ \left[\left(Z_{\text{nmax}-n} \right)^{\langle 2 \rangle} \right]_i & \text{otherwise} \end{cases}$ return xn </pre>	<pre> yn := nmax ← 2·ntraj for n ∈ 0..nmax for i ∈ 0..nsteps yn_{i,n} ← $\begin{cases} \left[\left(Z_n \right)^{\langle 4 \rangle} \right]_i & \text{if } n \leq \text{ntraj} \\ a - \left[\left(Z_{\text{nmax}-n} \right)^{\langle 4 \rangle} \right]_i & \text{otherwise} \end{cases}$ return yn </pre>
--	--

Stop trajectories at $x = d_1$ if they are intercepted by the control grid

```

xm :=
  xm ← xn
  for n ∈ 0..20
    intflag ← 0
    for i ∈ 0..nsteps
      intflag ← 1 if  $\left( x_{i,n} - d_1 \right)^2 + \left( y_{i,n} \right)^2 \leq r^2 \vee \left( x_{i,n} - d_1 \right)^2 + \left( a - y_{i,n} \right)^2 \leq r^2$ 
      xmi,n ← d1 if intflag = 1
    return xm

```

Calculate the cathode current density

$$K_1 := \frac{4 \cdot \epsilon_0}{9} \cdot \sqrt{2 \cdot 1.759 \cdot 10^{11} \cdot \text{C} \cdot \text{kg}^{-1}}$$

Parameters of the equivalent triode

$$V_e := \frac{V_s + D_s \cdot V_a}{1 + D_s \cdot \left(1 + \frac{d_3}{d_2}\right)}$$

Equation 6.91

$$V_e = 767.9 \text{ V}$$

$$d_e := \frac{d_1 + d_2 + D_s \cdot (d_1 + d_2 + d_3)}{1 + D_s \cdot \left(1 + \frac{d_3}{d_2}\right)}$$

Equation 6.92

$$d_e = 0.962$$

$$J_0(V_g) := \frac{K_1}{\text{mm}^2} \cdot \sqrt{1 + D_g} \cdot \frac{(V_g + D_g \cdot V_e)^{1.5}}{(d_1 + D_g \cdot d_e)^2}$$

Equation 6.93

$$J_0(V_g) = 1.97 \text{ A} \cdot \text{cm}^{-2}$$

Calculation of mean cathode current density when there is island formation


$$f1_g(x, y) := \frac{d}{dx} f_g(x, y)$$

$$D_E(y) := \frac{d_1 \cdot (1 - f1_g(0, y)) + d_e \cdot D_g}{(d_1 + d_e) \cdot f1_g(0, y) - d_1} \quad \text{Equation 6.94}$$


$$F_1(V_g, y) := \begin{cases} K_1 \cdot \frac{\sqrt{1 + D_E(y)} \cdot (V_g + D_E(y) \cdot V_e)^{1.5}}{(d_1 + D_E(y) \cdot d_e)^2} & \text{if } V_g + D_E(y) \cdot V_a \geq 0 \\ 0 & \text{otherwise} \end{cases}$$

$$J_1(V_g) := \frac{1}{a \cdot \text{mm}^2} \cdot \int_0^a F_1(V_g, y) dy \quad \text{Equation 6.96}$$

$$J_1(V_g) = 1.98 \text{ A} \cdot \text{cm}^{-2}$$



Vt_plot



Note: The horizontal and vertical scales of these figures are not normally the same as each other.