

## WS 3.5 Gap field

© 2017 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

### Section 3.5.3 Interaction Gap Fields

This worksheet can be used to investigate the effects of the field profile in the gap for varying gap lengths and fixed gap voltage

Gap voltage       $V_0 := 1$       Tunnel radius       $a := 1$

**a) Uniform field**

 Axial electric field at  $r = a$ 

$$E_0(z) := \begin{cases} \frac{V_0}{g} & \text{if } |z| < \frac{g}{2} \\ 0 & \text{otherwise} \end{cases}$$

 Limits of integration  
as approximation to  
infinity

lim := 100

Fourier transform

$$g_0(\beta) := V_0 \cdot \text{sinc}\left(\beta \cdot \frac{g}{2}\right)$$

Equation 3.78

Axial component of electric field within the gap

$$E_0(r, z) := \frac{1}{2 \cdot \pi} \cdot \int_{-\text{lim}}^{\text{lim}} \frac{I_0(\beta \cdot r)}{I_0(\beta \cdot a)} \cdot g_0(\beta) \cdot \exp(-j \cdot \beta \cdot z) d\beta$$

Equation 3.79

**b) Hyperbolic cosine field**

 Axial electric field at  $r = a$ 

$$E_1(k, z) := \begin{cases} \frac{k \cdot V_0 \cdot \cosh(k \cdot z)}{2 \cdot \sinh\left(k \cdot \frac{g}{2}\right)} & \text{if } |z| < \frac{g}{2} \\ 0 & \text{otherwise} \end{cases}$$

Equation 3.89

Fourier transform

$$g_1(k, \beta) := \left[ \frac{\sinh\left[(k + j \cdot \beta) \cdot \frac{g}{2}\right]}{(k + j \cdot \beta)} + \frac{\sinh\left[(k - j \cdot \beta) \cdot \frac{g}{2}\right]}{(k - j \cdot \beta)} \right] \cdot \frac{k \cdot V_0}{2 \cdot \sinh\left(k \cdot \frac{g}{2}\right)}$$

Axial component of electric field within the gap

$$E_1(k, r, z) := \frac{1}{2 \cdot \pi} \cdot \int_{-\text{lim}}^{\text{lim}} \frac{I_0(\beta \cdot r)}{I_0(\beta \cdot a)} \cdot g_1(k, \beta) \cdot \exp(-j \cdot \beta \cdot z) d\beta$$

**c) Knife edge field**Axial electric field at  $r = a$ 

$$E_2(z) := \begin{cases} \frac{V_0}{\pi} \cdot \frac{1}{\sqrt{\left(\frac{g}{2}\right)^2 - z^2}} & \text{if } |z| < \frac{g}{2} \\ 0 & \text{otherwise} \end{cases}$$

Equation 3.90

Fourier transform

$$g_2(\beta) := V_0 \cdot J_0\left(\beta \cdot \frac{g}{2}\right)$$

Axial component of electric field within the gap

$$E_2(r, z) := \frac{1}{2 \cdot \pi} \cdot \int_{-\lim}^{\lim} \frac{I_0(\beta \cdot r)}{I_0(\beta \cdot a)} \cdot g_2(\beta) \cdot \exp(-j \cdot \beta \cdot z) d\beta$$

Define the gap length

$$g \equiv 1$$

and the field shape  
parameter for a  
hyperbolic cosine field

$$k \equiv \frac{2}{g}$$

Plotting range

$$z1 := -2 \cdot a, -1.95 \cdot a .. 2 \cdot a$$




Figure 3.17