

WS 5.3 Spherical space-charge limited diode

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

Physical constants

Charge/mass ratio of the electron $\eta := 1.759 \cdot 10^{11} \cdot \text{C} \cdot \text{kg}^{-1}$

Rest energy of the electron (eV) $V_R := \frac{c^2}{\eta} = 510.947 \cdot \text{kV}$

Normalised variables

$$k_2 = \frac{-I}{4 \cdot \pi \cdot \epsilon_0 \cdot c \cdot V_R} \quad \text{Equation 5.82}$$

$$a_2 = \left(\frac{81}{32} \cdot k_2^2 \right)^{\frac{1}{3}} \quad \text{Equation 5.87}$$

$$a_2 \equiv 1$$

Langmuir's equations

$$\gamma(R) := \ln(R) \quad \text{Equation 5.83}$$

$$\alpha(R) := \gamma(R) - 0.3 \cdot \gamma(R)^2 + 0.075 \cdot \gamma(R)^3 - 0.0143182 \cdot \gamma(R)^4 + 0.0021609 \cdot \gamma(R)^5 - 0.00026791 \cdot \gamma(R)^6 \quad \text{Equation 5.85}$$

$$UL(R, a_2) := a_2 \cdot (|\alpha(R)|)^{\frac{4}{3}} \quad \text{Equation 5.86}$$

Acton's equations

$$UA(R, a_2) := a_2 \cdot (|\gamma(R)|)^{\frac{4}{3}} \cdot \left(1 - \frac{2}{5} \cdot \gamma(R) + \frac{3}{25} \cdot \gamma(R)^2\right) \quad \text{Equation 5.88}$$

$$UAR(R, a_2) := a_2 \cdot (|\gamma(R)|)^{\frac{4}{3}} \cdot \left[1 - \frac{2}{5} \cdot \gamma(R) + \frac{417}{25 \cdot 144} \cdot (|\gamma(R)|)^2\right] + a_2^2 \cdot (|\gamma(R)|)^{\frac{8}{3}} \cdot \left(-\frac{1}{14} + \frac{5}{7 \cdot 72} \cdot \gamma(R)\right) \quad \text{Equation 5.8*}$$

The differential equation for relativistic flow is (5.81)

$$\frac{d^2 U}{dR^2} + \frac{2}{R} \cdot \frac{dU}{dR} = \frac{k_2}{R^2} \cdot \frac{1+U}{\sqrt{2U+U^2}}$$

This can be expressed as a pair of simultaneous first order equations

$$\frac{d}{dR} U = U_1$$

Where $R = \frac{r}{r_0}$ $U = \frac{V}{V_R}$

$$\frac{d}{dR} U_1 = \frac{k_2}{R^2} \cdot \left(\frac{1+U}{\sqrt{2 \cdot U + U^2}} \right) - \frac{2 \cdot U_1}{R}$$

This equation is difficult to integrate numerically because of the singularity in the integrand close to $R = 1$ when $U = 0$. However, for small values of U , R is close to unity, dU/dR is close to zero and the equation can be approximated by

$$\frac{d^2U}{dR^2} = k_2 \frac{1}{\sqrt{2U}} \quad \text{which can be integrated to give} \quad R1(U) = 1 + \left(\frac{1}{\sqrt{2 \cdot k_2 \cdot \sqrt{2}}} \cdot \frac{4}{3} \cdot U^{\frac{3}{4}} \right)$$

This approximation can be used to start the solution from a point a little way from the cathode to avoid a divide by zero error when $U = 0$

When the cathode lies inside the anode

Let $U0 := 10^{-6}$



$R_{\max} := 5$

$R2 := 1, 1.2.. R_{\max}$

$$\begin{aligned} U1(a) := & \left| \begin{aligned} k_2 &\leftarrow \sqrt{\frac{32}{81} \cdot a^3} \\ R1 &\leftarrow 1 + \left(\frac{1}{\sqrt{2 \cdot k_2 \cdot \sqrt{2}}} \cdot \frac{4}{3} \cdot U0^{\frac{3}{4}} \right) \\ D1(R, U) &\leftarrow \left[\frac{U_1}{R^2 \cdot \left(\frac{1}{\sqrt{2 \cdot U_0}} \right)} - \frac{2 \cdot U_1}{R} \right] \\ U &\leftarrow \left(\frac{U0}{\sqrt{2 \cdot k_2 \cdot \sqrt{2 \cdot U0}}} \right) \\ U1 &\leftarrow \text{AdamsBDF}(U, R1, R_{\max}, 100, D1) \\ \text{return } &U1 \end{aligned} \right. \end{aligned}$$

$$\begin{aligned} U1R(a) := & \left| \begin{aligned} k_2 &\leftarrow \sqrt{\frac{32}{81} \cdot a^3} \\ R1 &\leftarrow 1 + \left(\frac{1}{\sqrt{2 \cdot k_2 \cdot \sqrt{2}}} \cdot \frac{4}{3} \cdot U0^{\frac{3}{4}} \right) \\ D1R(R, U) &\leftarrow \left[\frac{U_1}{R^2 \cdot \left[\frac{1 + U_0}{\sqrt{2 \cdot U_0 + (U_0)^2}} \right]} - \frac{2 \cdot U_1}{R} \right] \\ U &\leftarrow \left(\frac{U0}{\sqrt{2 \cdot k_2 \cdot \sqrt{2 \cdot U0}}} \right) \\ U1R &\leftarrow \text{AdamsBDF}(U, R1, R_{\max}, 100, D1R) \\ \text{return } &U1R \end{aligned} \right. \end{aligned}$$

The results are in matrices in which the first column is the independent variable, the second column is U and the third column its differential





When the anode lies inside the cathode

$$R_{3\min} := \frac{1}{R_{\max}} \quad R_3 := 1, 0.95 \dots R_{3\min}$$

$$\begin{aligned} \text{U2(a)} := & \left| \begin{aligned} k_2 &\leftarrow \sqrt{\frac{32}{81}} \cdot a^3 \\ R_3 &\leftarrow 1 + \left(\frac{1}{\sqrt{2 \cdot k_2 \cdot \sqrt{2}}} \cdot \frac{4}{3} \cdot U_0^{\frac{3}{4}} \right) \\ D2(R, U) &\leftarrow \left[\frac{U_1}{R^2 \cdot \left(\frac{1}{\sqrt{2 \cdot U_0}} \right)} - \frac{2 \cdot U_1}{R} \right] \\ U &\leftarrow \left(\frac{U_0}{-\sqrt{2 \cdot k_2 \cdot \sqrt{2 \cdot U_0}}} \right) \\ U2 &\leftarrow \text{AdamsBDF}(U, R_3, R_{3\min}, 100, D2) \\ \text{return } &U2 \end{aligned} \right. \end{aligned}$$

$$\begin{aligned} \text{U2R(a)} := & \left| \begin{aligned} k_2 &\leftarrow \sqrt{\frac{32}{81}} \cdot a^3 \\ R_3 &\leftarrow 1 + \left(\frac{1}{\sqrt{2 \cdot k_2 \cdot \sqrt{2}}} \cdot \frac{4}{3} \cdot U_0^{\frac{3}{4}} \right) \\ D2R(R, U) &\leftarrow \left[\frac{U_1}{R^2 \cdot \left[\frac{1 + U_0}{\sqrt{2 \cdot U_0 + (U_0)^2}} \right]} - \frac{2 \cdot U_1}{R} \right] \\ U &\leftarrow \left(\frac{U_0}{-\sqrt{2 \cdot k_2 \cdot \sqrt{2 \cdot U_0}}} \right) \\ U2R &\leftarrow \text{AdamsBDF}(U, R_3, R_{3\min}, 100, D2R) \\ \text{return } &U2R \end{aligned} \right. \end{aligned}$$







Figure 5.10(a) and (b)