

Worksheet 10.4 Multi-element depressed collector model (TWT)

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

This worksheet calculates the RF efficiency of a TWT with a multi-element depressed collector using an approximate trapezoidal spent-beam curve defined by the maximum and minimum normalised electron velocities at saturation. (see Figures 10.9 and 14.27).

$$V_{\max} := 1.1$$

$$V_{\min} := 0.5$$

Saturated efficiency

$$\eta_{\text{sat}} := 1 - \frac{V_{\max} + V_{\min}}{2}$$

$$\eta_{\text{sat}} = 20\%$$

$$N_{\text{stages}} := 5$$

Vc :=

	0
0	0
1	0.4
2	0.5
3	0.65
4	0.8
5	1
6	

Probability distribution for electron collection

probability :=

Constant
Linear
Sine
Sine squared



This section can be collapsed if required to allow the data and the results to be viewed on the same screen.

$$p(x) := \begin{cases} 1 & \text{if probability} = 1 \\ x & \text{if probability} = 2 \\ \sin\left(\frac{\pi \cdot x}{2}\right) & \text{if probability} = 3 \\ \sin\left(\frac{\pi \cdot x}{2}\right)^2 & \text{if probability} = 4 \end{cases}$$

Constant probability

$$\text{pc0}(\text{Ve}) := \begin{cases} V_{c_{N_stages+1}} \leftarrow 2 \cdot V_{c_{N_stages}} - V_{c_{N_stages-1}} \\ \text{for } n \in N_stages..0 \\ \text{pc}_n \leftarrow \begin{cases} 1 & \text{if } V_e \geq V_{c_n} \wedge V_e < V_{c_{n+1}} \\ 1 & \text{if } n = N_stages \wedge V_e \geq V_{c_{n+1}} \\ 1 & \text{if } n = 0 \wedge V_e < V_{c_1} \\ 0 & \text{otherwise} \end{cases} \\ \text{return pc} \end{cases}$$

Variable probability

$$\text{pc}(\text{Ve}) := \begin{cases} V_{c_{N_stages+1}} \leftarrow 2 \cdot V_{c_{N_stages}} - V_{c_{N_stages-1}} \\ \text{for } n \in N_stages..0 \\ \text{pc}_n \leftarrow \begin{cases} p\left(\frac{V_e - V_{c_n}}{V_{c_{n+1}} - V_{c_n}}\right) & \text{if } V_e \geq V_{c_n} \wedge V_e < V_{c_{n+1}} \\ 1 & \text{if } n = N_stages \wedge V_e \geq V_{c_{n+1}} \\ 1 & \text{if } n = 0 \wedge V_e < V_{c_1} \\ (1 - \text{pc}_{n+1}) & \text{if } n < N_stages \wedge (V_e \geq V_{c_{n+1}} \wedge V_e < V_{c_{n+2}}) \\ 0 & \text{otherwise} \end{cases} \\ \text{return pc} \end{cases}$$

Calculate the DC collector efficiency as a function of electron energy

$$\eta_{DC}(\text{Ve}) := \frac{1}{V_e} \cdot \sum_{n=0}^{N_stages} (pc(\text{Ve})_n \cdot V_{c_n})$$

Equation 10.26

Plot the probability of collection by each electrode as a function of the electron energy with rectangles showing constant probability for comparison.




Figure 10.10

Define an approximate trapezoidal spent-beam distribution

V_{max} is constant, V_{min} is defined by the saturated output power. X is the normalised output power

$$V_1(X) := (2 - V_{\max}) \cdot (1 - X) + X \cdot V_{\min}$$

$$V_s(X, \theta) := V_1(X) + (V_{\max} - V_1(X)) \cdot \frac{\theta}{\pi}$$

$$\eta_e(X) := 1 - \frac{1}{2}(V_{\max} + V_1(X))$$

$$I_s(\theta) := 1 \quad \Pi_s(\theta) := \frac{1}{\pi} \cdot \int_{\theta}^{\pi} I_s(\theta) d\theta$$

Calculate the total power entering the collector entering the collector normalised to the maximum RF output power

$$P_{\text{ent}}(X) := \frac{1}{\pi} \cdot \int_0^{\pi} I_s(\theta) \cdot V_s(X, \theta) d\theta$$

Check

$$1 - P_{\text{ent}}(0.5) = 0.1$$

$$\eta_e(0.5) = 0.1$$

Calculate the rf efficiency of the collector as a function of the RF grid voltage

$$P_{\text{rec}}(X) := \frac{1}{\pi} \cdot \int_0^{\pi} I_s(\theta) \cdot V_s(X, \theta) \cdot \eta_{\text{DC}}(V_s(X, \theta)) d\theta$$

Equation 10.30

$$\eta_c(X) := \frac{P_{\text{rec}}(X)}{P_{\text{ent}}(X)}$$

Compute the RF efficiency as function of the normalised output power

$$\eta_{\text{rf}}(X) := \frac{\eta_e(X)}{1 - \eta_c(X) \cdot (1 - \eta_e(X))}$$

Equation 10.13

Plotting ranges

$$\theta := 0, 0.1 \dots \pi$$

$$X := 0, 0.1 \dots 1$$



