

WS 6.2 Effective diode spacing in a triode

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

Section 6.4

The electric field at the cathode can be interpreted as the ratio of an effective voltage to an effective spacing

$$E_c = -\frac{V_g + D \cdot V_a}{d_1 + D \cdot (d_1 + d_2)} = \frac{V_e}{d_e} \qquad E_c = -\frac{V_g + D V_a}{d_1 + (d_1 + d_2) D} \qquad d = \frac{d_e}{d_1}$$

Then the space-charge limited current density is assumed to be given by

$$J = K \cdot \frac{V_e^{1.5}}{d_e^2} \qquad P = \frac{K}{d_1^2} \cdot P_n \qquad J = P \cdot (V_g + D \cdot V_a)^{1.5}$$

The possibilities offered in the literature give different results for the Perveance

$$P1(D, x) := \frac{1}{[1 + D \cdot (1 + x)]^2}$$

Equation 6.57 (Dow)

$$P2(D, x) := \frac{1}{[1 + D \cdot (1 + x)]^{1.5}}$$

Equation 6.58 (Bennett (b))

$$P3(D, x) := \frac{\sqrt{1 + D}}{[1 + D \cdot (1 + x)]^2}$$

Equation 6.56 (Walker)

Tellegen added a modification to account for space-charge

$$P4(D, x) := \frac{1}{\left[1 + D \cdot \left(1 + \frac{4}{3} \cdot x\right)\right]^{1.5}}$$


Equation 6.59 (Tellegen)

Fremlin calculated the perveance from a diode with the grid removed

$$P5(D, x) := \frac{1}{\left[1 + D \cdot (1 + x)^{\frac{4}{3}}\right]^{1.5}}$$

Equation 6.60 (Fremlin)

D1 := 0.1



$x1 := 10$ $x = \frac{d_2}{d_1}$ $x := -3, -2.9..0$ $D(x) := 10^x$





Figure 6.6

D1 := 0.01 D2 := 0.05 D3 := 0.1 x := 1..20



Lines Walker

Symbols Tellegen

Calculation of Fremlin's fig.7 using Walker's formula

$$a := 1.75 \cdot \text{mm}$$

$$d_1 := 1.7 \cdot \text{mm}$$

$$d_2 := 6.73 \cdot \text{mm} - d_1$$

$$d_2 = 5.03 \cdot \text{mm}$$

$$r := 0.0445 \cdot \text{mm}$$

$$e_m := 1.759 \cdot 10^{11} \cdot \text{C} \cdot \text{kg}^{-1}$$

$$\mu_{\text{Perv}} := \mu\text{A} \cdot \text{V}^{-1.5}$$

Experimental data points from Fremlin's fig.7

$$V_a := 200 \cdot \text{V}$$

$$K_1 := \frac{4}{9} \cdot \epsilon_0 \cdot \sqrt{2 \cdot e_m}$$

$$K_1 = 2.334 \cdot \mu\text{Perv}$$

$$D := \frac{-a}{2 \cdot \pi \cdot d_2} \cdot \ln \left(2 \cdot \sin \left(\frac{\pi \cdot r}{a} \right) \right)$$

$$D = 0.102$$

$$\frac{1}{D} = 9.841$$

$$J_1(V_g, V_a) := K_1 \cdot \frac{\sqrt{1 + D} \cdot (V_g + D \cdot V_a)^{\frac{3}{2}}}{[d_1 + D \cdot (d_1 + d_2)]^2}$$

$$V_g := \begin{pmatrix} -19.4 \\ -18.8 \\ -17.5 \\ -15.7 \\ -14.6 \\ -13.4 \\ -12.4 \\ -11.2 \\ -10.1 \\ -8.3 \\ -6.6 \\ -5.2 \\ -3.9 \\ -2.6 \\ -1.7 \\ -1.1 \\ -0.1 \end{pmatrix} \quad J_a := \begin{pmatrix} 0.07 \\ 0.10 \\ 0.22 \\ 0.44 \\ 0.58 \\ 0.78 \\ 0.95 \\ 1.17 \\ 1.41 \\ 1.75 \\ 2.09 \\ 2.45 \\ 2.80 \\ 3.16 \\ 3.40 \\ 3.55 \\ 3.86 \end{pmatrix}$$

x (cm)	y (cm)	Vg	J
7.05	0.15	-19.4	0.07
6.8	0.2	-18.8	0.10
6.35	0.45	-17.5	0.22
5.7	0.9	-15.7	0.44
5.3	1.2	-14.6	0.58
4.85	1.6	-13.4	0.78
4.5	1.95	-12.4	0.95
4.05	2.4	-11.2	1.17
3.65	2.9	-10.1	1.41
3	3.6	-8.3	1.75
2.4	4.3	-6.6	2.09
1.9	5.05	-5.2	2.45
1.4	5.75	-3.9	2.80
0.95	6.5	-2.6	3.16
0.6	7	-1.7	3.40
0.4	7.3	-1.1	3.55
0.05	7.95	-0.1	3.86

Fremlin fig.7 compared with Walker's formula




Figure 6.7