

WS 5.4 Planar diode with initial velocity

© 2018 Richard G Carter

This Mathcad 14 worksheet is designed to accompany the author's book "Microwave and RF Vacuum Electronic Power Sources", Cambridge University Press (2018). The section, equation, and figure numbers refer to the corresponding sections, equations, and figures in the book. Data input fields are highlighted in yellow and output fields are highlighted in green.

This resource is provided free of charge by Cambridge University Press with permission of the author, but is subject to copyright. You are permitted to view, print and download this resource for your own personal use only, provided any copyright lines are not removed or altered in any way. Any other use, including but not limited to, distribution of the resource in modified form, or via electronic or other media, is strictly prohibited unless you have permission from the author and provided you give appropriate acknowledgement of the source.

The contents of this sheet are provided for educational purposes only and no warranty is expressed or implied that they are suitable for use as professional design tools.

This sheet is based on:

Jaffe, G. (1944). "On the currents carried by electrons of uniform initial velocity." Physical Review **65**(3-4): 91.

$$U = \frac{V}{V_k}$$

$$Y(U) := \sqrt{1 + U}$$

The symbol Y is used in place of W to avoid redefining a Mathcad built-in variable.

Branch I: Potential increasing monotonically

$$\alpha_2(\alpha_1) := \frac{4}{3} \cdot (1 - 2 \cdot \alpha_1) \cdot (1 + \alpha_1)^{\frac{1}{2}}$$
Equation 5.104

$$X1(\alpha_1, U) := \frac{4}{3} \cdot (Y(U) - 2 \cdot \alpha_1) \cdot (Y(U) + \alpha_1)^{\frac{1}{2}} - \alpha_2(\alpha_1)$$
Equation 5.105

Branch II: Potential minimum but no reflection of electrons

$$X2a(\alpha_1, U) := \alpha_2(\alpha_1) - \frac{4}{3} (Y(U) - 2 \cdot \alpha_1) \cdot (Y(U) + \alpha_1)^{\frac{1}{2}}$$
Equation 5.106

$$X2b(\alpha_1, U) := \frac{4}{3} \cdot (Y(U) - 2 \cdot \alpha_1) \cdot (Y(U) + \alpha_1)^{\frac{1}{2}} + \alpha_2(\alpha_1)$$
Equation 5.107

Note: Setting $W = 1$ and $X = 0$ in (5.106) and (5.107) we find that α_3 and α_4 both satisfy (5.104). thus the can be replaced by α_2 in (5.106) and (5.107).

At the minimum of potential

$$X2_{\min}(\alpha_1) := \frac{4}{3} \cdot (1 - 2 \cdot \alpha_1) \cdot (1 + \alpha_1)^{\frac{1}{2}}$$
Equation 5.109

$$U2_{\min}(\alpha_1) := \alpha_1^2 - 1$$

Since $Y = -\alpha_1$ when $X = X_m$ (line before equation (5.108))

The current is space-charge limited at the maximum of the curve of constant U_a

$$\alpha_{\max}(U_a) := \frac{-\sqrt{1 + U_a}}{1 + \sqrt{1 + U_a}} \quad \text{Equation 5.111}$$

$$X_{\max}(U) := \frac{4}{3} \cdot (1 + \sqrt{1 + U})^{\frac{3}{2}} \quad \text{Equation 5.112}$$

$$\alpha_1 := -1, -0.99 \dots 0.2 \quad \alpha_{11} := -1, -0.99 \dots 4$$




Figure 5.13

The normalised anode potential is $U_a := 5$

Note:

1. There is a mistake in Figure 5.13 in the book. The upper curve corresponds to $U_a = 5$
2. Jaffe's parameter u_0 in his Figure 1 is given by

$$u_0 = \sqrt{1 + U_a}$$

Position of the maximum of the Branch II curve

$$X_{\max}(U_a) = 8.542$$

$$\alpha_{\max}(U_a) = -0.7101$$

Branch III: Virtual cathode which reflects some of the electrons

$$X_{3a}(R_3, U) := \frac{4}{3} \cdot \frac{1}{\sqrt{2 \cdot R_3 - 1}} \cdot \left(1 - Y(U)^{\frac{3}{2}}\right) \quad \boxed{\text{Equation 5.119}}$$

X3a refers to the region $0 < X < X_{\min}$;
 X3b refers to the region $X_{\min} < X < X_a$.
 R_3 is the ratio of the injected current
 to the anode current

$$X_{3b}(R_3, U) := \frac{4}{3} \cdot Y(U)^{\frac{3}{2}} + \frac{4}{3} \cdot \frac{1}{\sqrt{2 \cdot R_3 - 1}} \quad \boxed{\text{Equation 5.121}}$$

$$X_{3\min}(R_3) := \frac{4}{3} \cdot \frac{1}{\sqrt{2 \cdot R_3 - 1}} \quad \boxed{\text{Equation 5.118}}$$

Note: in the book $Y = 1$ on the previous
 line should be $W = 1$

$$X_3(R_3, U) := R_3 \cdot X_{2b}(0, U) \blacksquare$$

X_3 defines X in terms of the X in Branch II when $\alpha_1 = 0$

Normalise the potentials to U_{\max}

$$X_1(\alpha_1, U) := \frac{X_1(\alpha_1, U)}{X_1(\alpha_1, U_{\max})}$$

$$X_{2a}(\alpha_1, U) := \frac{X_{2a}(\alpha_1, U)}{X_{2b}(\alpha_1, U_{\max})}$$

$$X_{3a}(R_3, U) := \frac{X_{3a}(R_3, U)}{X_{3b}(R_3, U_{\max})}$$

$$X_{2b}(\alpha_1, U) := \frac{X_{2b}(\alpha_1, U)}{X_{2b}(\alpha_1, U_{\max})}$$

$$X_{3b}(R_3, U) := \frac{X_{3b}(R_3, U)}{X_{3b}(R_3, U_{\max})}$$

$$X_{2\min}(\alpha_1) := \frac{X_{2\min}(\alpha_1)}{X_{2b}(\alpha_1, U_{\max})}$$

$$X_{3\min}(R_3) := \frac{X_{3\min}(R_3)}{X_{3b}(R_3, U_{\max})}$$

Plot normalised potential against normalised position

Normalise the potentials to

$$U_{\max} \equiv 5$$

Monotonic increase (red)

$$\alpha_1 := -0.9$$


Potential minimum (blue)

$$\alpha_2 := -0.9$$

Virtual cathode (green)

$$R_3 := 2$$

$$u := -1, -0.995 \dots 5$$



When $\alpha = -1$ the space-charge minimum is at $X = 0$ and the potential curves for branches I and II are identical.

When $\alpha = 0$ and $R_3 = 1$ the potential curves for branches II and III are identical.

Monotonic increase

Potential minimum

Virtual cathode

$$X_{2\min}(\alpha_2) = 0.143$$

$$X_{3\min}(R_3) = 0.131$$

$$U_{2\min}(\alpha_2) = -0.19$$

$$X1(\alpha_1, U_a) = 5.872$$

$$X2b(\alpha_2, U_a) = 8.234$$

For space-charge limitation

$$X_{\max}(U_a) = 8.542$$

If d and V_k are fixed then the cathode current is proportional to X^2 .

The anode current normalised to the maximum limited by space-charge is

$$\left(\frac{X1(\alpha_1, U_a)}{X_{\max}(U_a)} \right)^2 = 0.473$$

$$\left(\frac{X2b(\alpha_2, U_a)}{X_{\max}(U_a)} \right)^2 = 0.929$$

$$\left(\frac{X3b(R_3, U_a)}{X_{\max}(U_a)} \right)^2 = 0.474$$

Plot anode current against injected current both normalised to the space-charge limited current

$$\alpha_{11} := -1, -0.99 \dots 10$$

The definition of X in equation (5.116) differs from that in equation (5.100). to make this clear we can replace X in (5.116) by X' so that


$$\alpha_{22} := -1, -0.99 \dots 0$$

$$X' = \sqrt{\frac{J_a}{J_i}} X$$

$$R3 := 1, 1.1 \dots 10$$

Then the injected current and the anode current normalised to the space-charge limited current are given by

$$J1_a(\alpha_1, U) := \left(\frac{X1(\alpha_1, U)}{X_{\max}(U)} \right)^2 \quad J2_a(\alpha_2, U) := \left(\frac{X2b(\alpha_2, U)}{X_{\max}(U)} \right)^2 \quad J3_i(R3, U) := \left(\frac{\sqrt{R3} \cdot X3b(R3, U)}{X_{\max}(U)} \right)^2 \quad J3_a(R3, U) := \left(\frac{X3b(R3, U)}{X_{\max}(U)} \right)^2$$



Normalised anode potential

$$U_a = 5$$