

Supplement 9.1. SAS commands for evaluations summarized in Tables 9.1 and 9.2

Brian R. Gray, US Geological Survey, Upper Midwest Environmental Sciences Center, La Crosse, Wisconsin, USA.

This supplement provides SAS commands for evaluating estimators of variance components (VCs) and variance partition components (VPCs) using linear models of data from two-way cross-classification designs. Corresponding routines were used for all scenarios summarized in Tables 9.1 and 9.2 of Chapter 9. A .sas format file containing the following commands is available on request from gitzenr@missouri.edu.

```

* PURPOSE: estimate variance components (VCs) and variance partition coefficients (VPCs) from linear models of data from
           2-way crossed classification designs;
* CREATED: 2 Apr 2010 by Brian Gray;
* REVISIONS: ;

/* THIS ALGORITHM IS PROVIDED WITHOUT WARRANTY, WHETHER EXPRESSED OR IMPLIED.  PLS SEND QUESTIONS AND CRITICISMS TO
*BRIAN GRAY AT brgray@usgs.gov */

* NOTES:
  * computer code for fitting cross-classified linear models in languages other than SAS (ie, HLM, MLwiN, R, STATA, as
  * well as SAS) using a common dataset is provided at http://www.ats.ucla.edu/stat/sas/examples/mlm\_ma\_hox/
  * "some cells empty" unbalanced scenarios may (rather crudely) be effected by manually replacing n=1 with n=0 under
  * the "data twoway" data step;

* DEFINE PARAMETER/DESIGN VALUES;
%let var_y = 1;
%let var_site = .3;
%let var_yr = .3;
%let var_sitebyyr = .15;
%let n = 5;
%let sites = 10;
%let years = 5;
%let siteproportion = .3;      * assign proportion sites w/in odd years with n=1 (see note above to move from 'all cells
                                * filled' to 'some cells empty' scenarios;
%let u0normal = 1;             * determine whether random group effects are normal (1) or random uniform (else) distributed;
%let simulations = 50;

options nocenter;
* delete all datasets (prevents using results from a previous scenario when all models for a given method fail to converge);
proc datasets library=work kill; run;
title1 "2-way design: sites = &sites, years=@years, reps = &n. var(yr)=&var_yr, var(site)=&var_site,
       var(sitebyyr)=&var_sitebyyr, var(yijk)=&var_y";

* GENERATE DATA;
* generate year effects;
data yr_effects;
  do sim = 1 to &simulations;
    do year=1 to &years;
      if &u0normal=1 then yr_effect=sqrt(&var_yr)*rannor(123);
      else yr_effect = sqrt(&var_yr)*(sqrt(12)*ranuni(234) - sqrt(12)/2);
      * random uniform with unit variance;
    do site=1 to &sites;
      output;
    end;
  end;
end;

```

```

        end;
    end;
end;

run;
proc sort data=yr_effects out=yr_effects_sort; by sim site year; run;

* generate site effects;
data site_effects;
    do sim = 1 to &simulations;
        do site = 1 to &sites;
            if &u0normal=1 then site_effect = sqrt(&var_site)*rannor(234);
            else site_effect = sqrt(&var_site)*(sqrt(12)*ranuni(234) - sqrt(12)/2);
            * random uniform with unit variance;

            do year= 1 to &years;
                if &u0normal=1 then sitebyyr_effect = sqrt(&var_sitebyyr)*rannor(345);
                else sitebyyr_effect = sqrt(&var_sitebyyr)*(sqrt(12)*ranuni(234) - sqrt(12)/2);
                * random uniform with unit variance;

                output;
            end;
        end;
    end;

run;

data twoway;
    merge yr_effects_sort site_effects;
    by sim site year;
    if mod(year, 2) then oddyear=1; else oddyear=0;
    sites=&sites; n=&n; siteproportion=&siteproportion;
    if oddyear and site gt siteproportion*sites then n=1;
    do i=1 to n;
        y = yr_effect + site_effect + sitebyyr_effect + sqrt(&var_y)*rannor(456);
        output;
    end;

run;

* ESTIMATE VARIANCE COMPONENTS BY METHOD;
ods listing close;
* estimate variance components using Type 3 SS's;
proc mixed data=twoway method=type3;* covtest cl;
    class year site;
    model y = ;
    random site year site*year; * slower format;
    by sim;
    ods output covparms=covparmstype3;
run;

```

```

* estimate variance components using ML (default = observed inverse Fisher information matrix);
proc mixed data=twoway method=ml;* covtest cl;
    class year site;
    model y = ;
    random int / sub=site;
    random int / sub=year;
    random int / sub=year*site;
    by sim;
ods output covparms=covparmsml;
run;

```

```

* estimate variance components using REML (default = observed inverse Fisher information matrix);
proc mixed data=twoway method=reml;* covtest cl;
    class year site;
    model y = ;
    random int / sub=site;
    random int / sub=year;
    random int / sub=year*site;
    by sim;
ods output covparms=covparmsreml;
run;
ods listing;

```

```

* CALCULATE SUMMARY STATISTICS;
* append datasets;
data covparms_row;
    set covparmstype3(in=type3) covparmsml(in=ML) covparmsreml(in=REML);
    if type3 then method="1Type3"; else if ML then method="2ML"; else method="3REML";
    if covparm="Residual" then covparm="z_residual";
    if method in ("2ML", "3REML") then covparm=subject;
    if method in ("2ML", "3REML") and subject="" then covparm="z_residual";
    * variance assignments/calculations;
    varhat=estimate; if method="1Type3" and estimate lt 0 then varhat=0;
    if 0 le estimate lt 1E-4 then varhat0=1; else varhat0=0;
    if estimate < 0 then varhatneg=1; else varhatneg=0;
    SDhat=sqrt(varhat);
    * precision assignment;
    *SEhat=stderr; * requires unremarking covtest options;
    * calculate VPC estimates;
    VPC_site = lag3(varhat) / (varhat + lag(varhat)+lag2(varhat) + lag3(varhat));
    if covparm ne "z_residual" then VPC_site=.;
    VPC_yr = lag2(varhat) / (varhat + lag(varhat)+lag2(varhat) + lag3(varhat));
    if covparm ne "z_residual" then VPC_yr=.;
    VPC_siteyr = (lag(varhat)+lag2(varhat) + lag3(varhat)) / (varhat + lag(varhat)+lag2(varhat) + lag3(varhat));
    if covparm ne "z_residual" then VPC_siteyr=.;
    keep sim method covparm varhat varhat0 varhatneg SDhat VPC_site VPC_yr VPC_siteyr;* SEhat;

```

```

run;
proc sort data=covparms_row out=covparms_row_sort; by covparm method sim; run;

* calculate variance component stats;
title1 "2-way design: sites = &sites, years=&years, n = &n, var_yij=&var_y, var(yr)=&var_yr, var(site)=&var_site,
var(sitebyyr)=&var_sitebyyr, sims=&simulations";
title2 "Variance component stats";
proc means data=covparms_row_sort noprint;
    var varhat SDhat varhat0 varhatneg /*SEhat*/ ;
    output out=varcompstats mean=meanvarhat meanSDhat meanvarhat0 meanvarhatneg /*meanSEvarhat*/ stddev=SE_varhat SE_SDhat
        /*SESEvarhat*/;
    by covparm method;
run;
* add pct convergence;
data varcompstats2;
    set varcompstats(drop=_TYPE_);
    pctconverge=_freq_/&simulations;
proc print data=varcompstats2 noobs;
    format _numeric_ 8.3 pctconverge 8.2 _freq_;
    var covparm method _freq_ pctconverge meanvarhat /*meanSEvarhat*/ SE_varhat meanvarhat0 meanvarhatneg meanSDhat
        SE_SDhat;
run;

* calculate VPC stats;
title2 "VPC stats";
proc means data=covparms_row noprint;
    var VPC_site VPC_yr VPC_siteyr;
    output out=VPCstats mean=meanVPCsite meanVPCyr meanVPCsiteyr stddev=SE_VPCsite SE_VPCyr SE_VPCsiteyr
        median=medVPCsite medVPCyr medVPCsiteyr qrange= iqrVPCsite iqrVPCyr iqrVPCsiteyr;
    by method;
    where covparm = "z_residual";
run;
proc print data=VPCstats noobs;
    format _numeric_ 8.2 _freq_;
    var method _freq_ meanVPCsite SE_VPCsite medVPCsite iqrVPCsite meanVPCyr SE_VPCyr medVPCyr iqrVPCyr meanVPCsiteyr
        SE_VPCsiteyr medVPCsiteyr iqrVPCsiteyr;
run;

* PLOT ESTIMATES;
* plot variance/SD estimates;
proc boxplot data=covparms_row_sort; plot SDhat*method; by covparm; run;
* plot VPC estimates;
proc boxplot data=covparms_row; plot (VPC_site VPC_yr VPC_siteyr)*method; run;

```